Colour: Sablé 100 Noir



General Features

Description: lantern designed to house the LED technology

Insulation class: class II

Rated voltage: 220-240 V 50 Hz

Protection Grade: IP66
Impact protection: IK08

Surge protection device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM

Power Factor: > 0.90

Ambient temperature Ta: -30°C +50°C

Weight: 8.00 kg

Max exposed surface: 0,19 m²

Lateral exposed surface: 0,09 m²


Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Driver: included

Driver lifetime: >100.000 h @ Ta 25°C (0,2% / 1000h)

Marks and Certifications: ENEC / CE



I max= 357 cd/Klm -90 90

Performance Data*

Source flux:	3760 lm
Source power:	19 W
Source efficiency:	197 lm/W
Device flux:	3005 lm
Device power:	22 W
Appliance efficiency:	136 lm/W
Glare Index Category:	D6



Product Sheet

Rev 08/05/2024

Agathos Ceiling Suspension

Color Temperature: 3000 K Type of optics: RS-02 Rotosymmetric Beam 01AG3B242924CHM4

Colour: Sablé 100 Noir

Optical System
Source: LED R1
Color Temperature: 3000 K
Color Rendering Index (CRI): ≥ 70
Chromatic consistency (SDCM): ≤ 3
Type of optics: RS-02 Rotosymmetric Beam
Optical group life: >100.000 h @ Ta 25°C L90B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Light intensity category: G*6

Installation and maintenance

Installation: arcade

Normative References

Fixing: arm or chain suspended - standard on arms with a 3/4" female gas attachment; on Ø 60 mm arms using the required accessory (code 01AG902C0); fastening system (code 01AG903C0) for catenary suspension system.

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Replaceable wiring plate: removable plate

EN60598-1 / EN60598-2-3 / EN62471 / EN61547

Replaceable optical unit: each LED module is replaceable

Disconnector: automatic (with terminal section 2.5 mm²)

Power supply compartment: independent from the optical system

Flow adjustment	On request	
Virtual Midnight Teaching	X	
Constant flow output (CLO)	X	
DALI control	X	
Power line telemanagement (PLC)	X	
Wireless remote management	X	

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: extra clear tempered flat glass 4 mm

Lenses: high-transparency PMMA

Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: zinc-plated steel

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

Colors

Sablé 100 Noir	Code: 01AG3B242924CHM4



Product Sheet


Rev 08/05/2024

Agathos Ceiling Suspension

Color Temperature: 3000 K Type of optics: RS-02 Rotosymmetric Beam 01AG3B242924CHM4

Colour: Sablé 100 Noir

Complements



01AG903C0

Suspension hook on chain

NOTES

*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering. In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.

