




**General Features**

Description:	Recessed product
Insulation class:	class III
Rated voltage:	500 mA
Protection Grade:	IP66
Impact protection:	IK08
Power Factor:	> 0.9
Ambient temperature Ta:	-30°C +50°C
Weight:	1.00 kg
Driver:	remote (to be ordered separately)
Marks and Certifications:	CE



**Performance Data\***

LED Current:	500 mA
Source flow:	815 lm
Source power:	6.5 W
Source efficiency:	125 lm/W
Device flow:	250 lm
Device power:	7.5 W
Appliance efficiency:	33 lm/W
Glare Index Category:	D6

**Product Sheet**

Rev. 17/01/2023

**Aplos Wall-Recessed**

Options: DALI

Color Temperature: 2700 K

Type of optics: AS-D

**06AP1A84847DV**

Colour: White RAL9003

**Optical System**

Source: 8 LEDs

Color Temperature: 2700 K

Color Rendering Index (CRI):  $\geq 80$ Chromatic consistency (SDCM):  $\leq 3$ 

Type of optics: AS-D

Optical group life: &gt;60.000h @Ta25°C L80B10

Photobiological safety class: EXEMPT GROUP

**Normative References**

EN60598-1 / EN60598-2-3 / EN62471 / EN61547

**Installation and maintenance**

Installation: wall recessed

Wiring: rear cable entry, pre-wiring with outgoing cable

**Flow adjustment**

Standard

DALI control

X

**Materials**

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content &lt; 1%)

Screen: polycarbonate

Optical Collimator: nylon PA66

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

**Colors** White RAL9003Code: **06AP1A84847DV**

**Product Sheet**

Rev. 17/01/2023

**Aplos Wall-Recessed**


Options: DALI

Color Temperature: 2700 K

Type of optics: AS-D


**06AP1A84847DV**

Colour: White RAL9003

**Complements**

06LX900X0

B176 DALI driver 16W IP20



06AP901X0

M1 CONNECTOR

IP68 2P CL.III - DALI

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.