



### General Features

Description: recessed LED product

Insulation class: class III

Rated voltage: 24Vdc

Protection Grade: IP67

Impact protection: IK10

Power Factor: > 0.9

Ambient temperature Ta: -30°C +50°C

Weight: 0,4 kg

Drivers: to be ordered separately

Marks and Certifications: CE



H (m)	Ø (m)	Em (lux)
1	0.5	147
2	0.9	37
3	1.5	16
4	2	9
5	2.3	6

### Performance Data\*

Source flow:	90 lm
Source power:	0.6 W
Source efficiency:	150 lm/W
Device flow:	70 lm
Device power:	0.6 W
Appliance efficiency:	117 lm/W

**Product Sheet**

Rev. 17/01/2023

**Chara Ceiling-Recessed**

Color Temperature: 3000 K

Type of optics: medium beam 25°

**06CH1A139A6XS**Colour: sandblasted  
stainless steel AISI  
316L**Optical System**

Source: LED

Color Temperature: 3000 K

Color Rendering Index (CRI):  $\geq 80$ Color Consistency (SDCM):  $\leq 3$ 

Type of optics: medium beam 25°

Optical group life: &gt;50.000h @Ta25°C L80B10

Photobiological safety class: EXEMPT GROUP

**Normative References**

EN60598-1 / EN60598-2-1 / EN62471 / EN61547

**Installation and maintenance**

Installation: ceiling, walk over, wall-recessed

Fixing: springs

Wiring: pre-wired product with M8x1 screw connector;  
cable length of 1 m**Flow adjustment**

On request

DALI control

X


**Materials**Body: micro-shot peened stainless steel AISI 316L with  
sanded finish

Screen: tempered flat glass

Lenses: high-transparency PMMA

Seals: anti-age silicone

Screws: stainless steel AISI 304

Finish: AISI 316L stainless steel frame with sandblasted and  
shoot peened finish**Colors** sandblasted stainless  
steel AISI 316LCode: **06CH1A139A6XS**

## Product Sheet

Rev. 17/01/2023

## Chara Ceiling-Recessed

Color Temperature: 3000 K

Type of optics: medium beam 25°

## 06CH1A139A6XS

Colour: sandblasted  
stainless steel AISI  
316L

## Complements



06CH903X0

B147 Driver  
10W-24V IP67



06CH904X0

B148 Driver  
60W-24V IP67



06KS918C0

B137 2 - way connector IP68



06CH902XX0

B131 Springs  
for ceiling installation



06CH906X0

B198 Kit in/out  
cable 1 m 24 V with junction box



06KS909C0

B89 Connector 4 way IP68



06LL914AB0

DALI driver  
150W-24V IP67

---

**Product Sheet**

Rev. 17/01/2023

**Chara Ceiling-Recessed**

Color Temperature: 3000 K

Type of optics: medium beam 25°

**06CH1A139A6XS**Colour: sandblasted  
stainless steel AISI  
316L

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.