



### General Features

Description: wall-mounted LED product

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK08

Power Factor: > 0.9

Ambient temperature Ta: -30°C +50°C

Weight: 1.45 kg

Max exposed surface: 0,012 m<sup>2</sup>

Drivers: included

Marks and Certifications: CE



### Performance Data\*

LED Current:	640 mA
Source flow:	1775 lm
Source power:	15.5 W
Source efficiency:	115 lm/W
Device flow:	700 lm
Device power:	17.5 W
Appliance efficiency:	40 lm/W

**Product Sheet**

Rev. 15/05/2023

**Grapho**

Options: DALI

Color Temperature: 4000 K

Type of optics: 2x blade 4°x17° + 2x ultra-wide beam  
100°x60°**06GR4A80049DHL**

Colour: White RAL9003

**Optical System**

Source: LED

Color Temperature: 4000 K

Color Rendering Index (CRI):  $\geq 80$ Color Consistency (SDCM):  $\leq 3$ Type of optics: 2x blade 4°x17° + 2x ultra-wide beam  
100°x60°

Optical group life: &gt;60.000h @Ta25°C L80B10

Photobiological safety class: EXEMPT GROUP

**Normative References**

EN60598-1 / EN60598-2-5 / EN62471 / EN61547

**Installation and maintenance**

Installation: wall

Wiring: Rear cable entry, predisposition to in and out  
setup**Flow adjustment**

Standard

DALI control

X

**Materials**Body: die-cast aluminium alloy UNI EN AB 47100 (copper  
content < 1%)

Screen: UV stabilized technopolymer

Lenses: high-transparency PMMA

Fixing system: base die-cast aluminium alloy UNI EN AB  
47100 (copper content < 1%)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 316

Finish: phospho-chromatation treated and polyester  
powder-coated in 16 phases to increase weather resistance**Colors** White RAL9003Code: **06GR4A80049DHL**

---

**Product Sheet**

Rev. 15/05/2023

**Grapho**

Options: DALI

Color Temperature: 4000 K

Type of optics: 2x blade 4°x17° + 2x ultra-wide beam  
100°x60°**06GR4A80049DHL**Colour: White RAL9003

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.