



**General Features**

Description:	LED street fixture
Insulation class:	class II
Rated voltage:	220-240 V 50/60 Hz
Protection Grade:	IP66
Impact protection:	IK08
Surge protection device:	integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM
Power Factor:	> 0.9
Ambient temperature Ta:	-30°C +50°C
Weight:	6.50 kg
Max exposed surface:	0,13 m <sup>2</sup>
Lateral exposed surface:	0,036 m <sup>2</sup>
Common mode surge protection:	10 kV
Overvoltage protection differential mode:	10 kV
Drivers:	included
Marks and Certifications:	ENEC / CE



**Performance Data\***

LED Current:	350 mA
Source flow:	2915 lm
Source power:	15.5 W
Source efficiency:	188 lm/W
Device flow:	2505 lm
Device power:	18 W
Appliance efficiency:	139 lm/W
Glare Index Category:	D6

### Optical System

Source: LED R1,3

Color Temperature: 3000 K

Color Rendering Index (CRI):  $\geq 70$

Color Consistency (SDCM):  $\leq 4$

Type of optics: street asymmetrical ME-01

Optical group life: >160.000h @700mA @Ta25°C TM21  
L80B20 >160.000h @700mA @Ta25°C TM21 L80B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G\*3

### Normative References

EN60598-1 / EN60598-2-3 / EN62471 / EN61547

### Installation and maintenance

Installation: side pole / arm

Pole diameter: Ø 46 - 60 - 76 mm

Tilt: post top 0 +20° (step 5°); arm 0 -20° (step 5°)

Fixing: 2 x AISI 304 stainless steel securing bolts

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Replaceable wiring plate: tool less

Replaceable optical unit: tool less

Disconnecter: automatic (with terminal section 2.5 mm<sup>2</sup>)

Power supply compartment: independent from the optical group

### Flow adjustment

Standard On request

Virtual Midnight Teaching X

Constant flow output (CLO) X

Adjusting 1-10V X

DALI control X

Mains voltage variation X

Pilot line X

Power line telemanagement (PLC) X

Wireless remote management X

Provision for motion/light sensors X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: tempered flat glass 4 mm

Lenses: high-transparency PMMA

Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: self-extinguishable technopolymer V0

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ Grey RAL9006

Code: **01KI1B63932AHM4**

## Complements



06GN902C0

Wall-mounted plate with a 90° inclination for fixtures with Ø 60 mm fastening part. Colour: Sablé 100 Noir.



06GN901C0

Corner plate with a 90° inclination for fixtures with Ø 60 mm fastening part. Colour: Sablé 100 Noir.



01AK921A0

B1 Double tubular arm Ø 60 mm for poles Ø 60-76 mm. L=550 mm. Colour: grey RAL9006.



01AK922A0

B2 Double tubular arm Ø 60 mm for poles Ø 60-76 mm. L=550 mm. Colour: grey RAL9006.



01AK951A0

B1-P Tubular wall-mounted arm Ø 60 mm. L=550 mm. Colour: grey RAL9006.



01AK969A0

B74 Single tubular arm Ø 60 mm with tensioning rod for poles Ø 60-76 mm. L=1050 mm (pole center-fitting center). Colour: grey RAL9006.



01AK968A0

B59 Double tubular arm Ø 60 mm with tensioning rod for poles Ø 60-76 mm. L=1050 mm (pole center-fitting center). Colour: grey RAL9006.

---

**Product Sheet**

Rev. 17/11/2021

**Kai Pole System**

Size: small

Color Temperature: 3000 K

Type of optics: street asymmetrical ME-01

**01KI1B63932AHM4**Colour: Grey RAL9006

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of  $\pm 7\%$ .

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.