



**General Features**

Description: LED fitting for lighting façades, paths and urban spaces
Insulation class: Class II
Rated voltage: 220-240 V 50/60 Hz
Protection Grade: IP66
Impact protection: IK07
Surge protection device: integrated 2kV-4kV
Power Factor: > 0.95
Ambient temperature Ta: -30°C +50°C
Weight: 4.5 kg
Max exposed surface: 0.04 m <sup>2</sup>
Lateral exposed surface: 0.015 m <sup>2</sup>
Common mode surge protection: 2 kV
Overvoltage protection differential mode: 4 kV
Driver: included
Marks and Certifications: CE



**PRO 70**



**Performance Data\***

Source flow:	2200 lm
Source power:	16 W
Source efficiency:	138 lm/W
Device flow:	1475 lm
Device power:	18 W
Appliance efficiency:	82 lm/W

**Product Sheet**

30/07/2024

**Kinetic Ceiling**

Size: Monoemission

Color Temperature: 4000 K

Type of optics: U-D 90° Diffused beam

**06K11C01200C4DHL**

Colour: Sablé 100 Noir

**Optical System**

Source: 5 LED

Color Temperature: 4000 K

Color Rendering Index (CRI):  $\geq 80$ Chromatic consistency (SDCM):  $\leq 3$ 

Type of optics: U-D 90° Diffused beam

Optical group life: &gt;60.000 h @ Ta 25°C L80B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

**Normative References**EN60598-1 / EN60598-2-3 / EN61547 / EN62471 / EN55015 /  
EN61000-3-2 / EN61000-3-3**Installation and maintenance**

Installation: wall, ceiling, ground

Tilt: -90° +130° continuously adjustable

Ø power cable: 7 ÷ 13 mm

Cable Gland: M20

Power supply compartment: independent from the  
optical group**Flow adjustment**

Standard

DALI control

X

**Materials**Body: die-cast aluminium alloy UNI EN AB 47100 (copper  
content < 1%)

Screen: tempered flat glass 4 mm

Lenses: high-transparency PMMA

Seals: anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester  
powder-coated in 16 phases to increase weather resistance**Colors**

■ Sablé 100 Noir

Code: **06K11C01200C4DHL**

## Product Sheet

30/07/2024

## Kinetic Ceiling

Size: Monoemission

Color Temperature: 4000 K

Type of optics: U-D 90° Diffused beam

**06KI1C01200C4DHL**

Colour: Sablé 100 Noir

## Complements



06KI911X0

Kit converter medium beam 30°x18°

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.