



**General Features**

|   |
|---|
| Description: LED fitting for lighting façades, paths and urban spaces |
| Insulation class: class II  |
| Rated voltage: 220-240 V 50/60 Hz                                     |
| Protection Grade: IP66  |
| Impact protection: IK09   |
| Surge protection device: integrated 10kV-10kA                         |
| Power Factor: > 0.95  |
| Ambient temperature Ta: -30°C +50°C                                   |
| Weight: 6 kg  |
| Max exposed surface: 0.119 m <sup>2</sup>                             |
| Lateral exposed surface: 0.026 m <sup>2</sup>                         |
| Common mode surge protection: 10 kV                                   |
| Overvoltage protection differential mode: 10 kV                       |
| Driver: included  |
| Marks and Certifications: ENEC / ENEC+ / CE                           |



| H (m) | Ø (m) | Em (lux) |
|-------|-------|----------|
| 1     | 2     | 565      |
| 2     | 4.2   | 141      |
| 3     | 6.3   | 63       |
| 4     | 8.5   | 35       |
| 5     | 10.6  | 23       |

**Performance Data\***

|                       |          |
|-----------------------|----------|
| LED Current:          | 1000 mA  |
| Source flow:          | 8545 lm  |
| Source power:         | 67.5 W   |
| Source efficiency:    | 126 lm/W |
| Device flow:          | 6325 lm  |
| Device power:         | 74 W     |
| Appliance efficiency: | 85 lm/W  |
| Glare Index Category: | D5       |

### Optical System

Source: LED L6

Color Temperature: 3000 K

Color Rendering Index (CRI):  $\geq 80$

Chromatic consistency (SDCM):  $\leq 3$

Type of optics: U-D 90° Diffused beam

Optical group life: >100.000h @ Ta 25°C L90B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G\*6

BUG rating: B2-U0-G1

### Normative References

EN60598-1 / EN60598-2-5 / EN62471 / EN61547

### Installation and maintenance

Installation: wall, ceiling, ground, pole side

Tilt: (wall, ground) with adjustable joint can be tilted from -90° to +90° and rotated from -15° to +15°; the pointing and locking system is continuously adjustable; (pole side) with adjustable joint can be tilted from -70° to +90° and rotated by 0° / 180°; the pointing and locking system is continuously adjustable.

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Power supply compartment: independent from the optical group

### Flow adjustment

Standard

DALI control

X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: tempered flat glass 4 mm

Lenses: high-transparency PMMA

Seals: anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ Sablé 100 Noir

Code: **06LN2C4109C4CHL**

## Complements




06LN901C0

B225 Adjustable joint.  
Colour: Sable 100 Noir.



06LN914J0

B246 Kit metal anchors LEVANTE 2.0



06LN912B0

B240 Lightshade visor kit.  
Levante 2.0 small. Colour: black  
RAL9005.

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.