



General Features

Description: LED floodlight

Insulation class: class II

Rated voltage: 230 V 50 Hz

Protection Grade: IP66

Impact protection: IK07

Surge protection device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM

Power Factor: > 0.90

Ambient temperature Ta: -30°C +50°C

Weight: 8.00 kg

Max exposed surface: 0,17 m²


Lateral exposed surface: 0,04 m²

Common mode surge protection: 10 kV

Overtoltage protection differential mode: 10 kV

Drivers: included

Marks and Certifications: ENEC / CE



Performance Data*

| | | | |
|-----------------------|----------|----------|----------|
| LED Current: | 700 mA | 525 mA | 350 mA |
| Source flow: | 12620 lm | 9965 lm | 7020 lm |
| Source power: | 72 W | 53 W | 34.5 W |
| Source efficiency: | 175 lm/W | 188 lm/W | 203 lm/W |
| Device flow: | 10855 lm | 8570 lm | 6020 lm |
| Device power: | 78 W | 58.5 W | 39 W |
| Appliance efficiency: | 139 lm/W | 146 lm/W | 154 lm/W |
| Glare Index Category: | D6 | D6 | D6 |

Optical System

Source: LED R3

Color Temperature: 4000 K

Color Rendering Index (CRI): ≥ 70

Color Consistency (SDCM): ≤ 4

Type of optics: rotosymmetrical LR-20

Optical group life: >160.000h @700mA @Ta25°C TM21
L80B20 >160.000h @700mA @Ta25°C TM21 L80B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G*6

Normative References

EN60598-1 / EN60598-2-3 / EN60598-2-5 / EN62471 /
EN61547

Installation and maintenance

Installation: wall / ground / pole

Pole diameter: Ø 60 - 76 - 102 mm

Tilt: fastened or adjustable with step 15°

Fixing: adjustable bracket with click positioning and a 15°
step

Ø power cable: 10 ÷ 14 mm

Cable gland: PG16

Flow adjustment

Standard On request

Virtual Midnight Teaching X

Constant flow output (CLO) X

Adjusting 1-10V X

DALI control X

Mains voltage variation X

Pilot line X

Power line telemanagement (PLC) X

Wireless remote management X

Provision for motion/light sensors X

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper
content < 1%)

Lenses: PMMA

Seals: extruded anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester
powder-coated in 16 phases to increase weather resistance

Colors

■ Sablé 100 Noir

Code: **06LV6D60042CHM3**

Complements



06AK953C0

I1 Spike for ground installation
Colour: Sablé 100 Noir.



06AK903C0

L3 Joint kit
single for Ø 60-76 mm poles. Colour:
Sablé 100 Noir.



06AK904C0

L4 Joint kit
double for Ø 60-76 mm poles. Colour:
Sablé 100 Noir.



06AK954C0

L10 Joint LEVANTE MEDIUM
for Ø 60 mm pole. Colour: Sablé 100
Noir.



06AK951C0

B1-P Wall-mounted arm.
Colour: Sablé 100 Noir.

NOTES

*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.