



General Features

|   |   |
|---|---|
| Description:                              | LED floodlight  |
| Insulation class:                         | class II  |
| Rated voltage:                            | 230 V 50 Hz   |
| Protection Grade:                         | IP66  |
| Impact protection:                        | IK07  |
| Surge protection device:                  | integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM |
| Power Factor:                             | > 0.90  |
| Ambient temperature Ta:                   | -30°C +50°C   |
| Weight:                                   | 8.00 kg   |
| Max exposed surface:                      | 0,17 m²   |
| Lateral exposed surface:                  | 0,04 m²   |
| Common mode surge protection:             | 10 kV   |
| Overvoltage protection differential mode: | 10 kV   |
| Driver:                                   | included  |
| Marks and Certifications:                 | CE  |



Performance Data\*

|                       |          |          |          |
|-----------------------|----------|----------|----------|
| LED Current:          | 700 mA   | 525 mA   | 350 mA   |
| Source flow:          | 11780 lm | 9300 lm  | 6555 lm  |
| Source power:         | 72 W     | 53 W     | 34.5 W   |
| Source efficiency:    | 164 lm/W | 175 lm/W | 190 lm/W |
| Device flow:          | 10135 lm | 8000 lm  | 5640 lm  |
| Device power:         | 78 W     | 58.5 W   | 39 W     |
| Appliance efficiency: | 130 lm/W | 137 lm/W | 145 lm/W |
| Glare Index Category: | D6       | D6       | D6       |

### Optical System

|   |
|---|
| Source: LED R3  |
| Color Temperature: 3000 K   |
| Color Rendering Index (CRI): $\geq 70$  |
| Chromatic consistency (SDCM): $\leq 4$  |
| Type of optics: rotosymmetrical LR-20   |
| Optical group life: >160.000h @700mA @Ta25°C TM21 L80B20 >160.000h @700mA @Ta25°C TM21 L80B10 |
| Photobiological safety class: EXEMPT GROUP  |
| ULOR: 0%  |
| DLOR: 100%  |
| Light intensity category: G*6   |

### Normative References

EN60598-1 / EN60598-2-3 / EN60598-2-5 / EN62471 / EN61547

### Installation and maintenance

|  |
|--|
| Installation: wall / ground / pole                               |
| Pole diameter: Ø 60 - 76 - 102 mm                                |
| Tilt: fastened or adjustable with step 15°                       |
| Fixing: adjustable bracket with click positioning and a 15° step |
| Ø power cable: 10 ÷ 14 mm  |
| Cable gland: PG16  |

### Flow adjustment

Standard On request

|                                    |   |
|------------------------------------|---|
| Virtual Midnight Teaching          | X |
| Constant flow output (CLO)         | X |
| Adjusting 1-10V                    | X |
| DALI control                       | X |
| Mains voltage variation            | X |
| Pilot line                         | X |
| Power line telemanagement (PLC)    | X |
| Wireless remote management         | X |
| Provision for motion/light sensors | X |

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Lenses: PMMA

Seals: extruded anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ Sablé 100 Noir Code: **06LV6D60942CHM3**

## Complements



06AK953C0

I1 Spike for ground installation  
Colour: Sablé 100 Noir.



06AK903C0

L3 Joint kit  
single for Ø 60-76 mm poles. Colour:  
Sablé 100 Noir.



06AK904C0

L4 Joint kit  
double for Ø 60-76 mm poles. Colour:  
Sablé 100 Noir.



06AK954C0

L10 Joint LEVANTE MEDIUM  
for Ø 60 mm pole. Colour: Sablé 100  
Noir.



06AK951C0

B1-P Wall-mounted arm.  
Colour: Sablé 100 Noir.

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.