





**General Features**

Description:	LED luminaire
Insulation class:	class II
Rated voltage:	230 V 50 Hz
Protection Grade:	IP66
Impact protection:	IK07
Power Factor:	> 0.90
Ambient temperature Ta:	-30°C +50°C
Weight:	3.00 kg
Max exposed surface:	0,08 m <sup>2</sup>
Lateral exposed surface:	0,0165 m <sup>2</sup>
Common mode surge protection:	6 kV
Overvoltage protection differential mode:	10 kV
Drivers:	included
Marks and Certifications:	ENEC / CE



**Performance Data\***

LED Current:	700 mA	525 mA	350 mA
Source flow:	3995 lm	3140 lm	2205 lm
Source power:	24 W	17.5 W	11.5 W
Source efficiency:	166 lm/W	179 lm/W	192 lm/W
Device flow:	3240 lm	2545 lm	1785 lm
Device power:	27 W	20 W	13.5 W
Appliance efficiency:	120 lm/W	127 lm/W	132 lm/W
Glare Index Category:	D1	D2	D3

### Optical System

Source: LED R1
Color Temperature: 3000 K
Color Rendering Index (CRI): $\geq 70$
Color Consistency (SDCM): $\leq 4$
Type of optics: street
Optical group life: >160.000h @700mA @Ta25°C TM21 L80B20 >160.000h @700mA @Ta25°C TM21 L80B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Light intensity category: G*2

### Normative References

EN60598-1 / EN60598-2-3 / EN60598-2-5 / EN62471 /  
EN61547

### Installation and maintenance

Installation: wall / ground / pole
Pole diameter: Ø 60 - 76 - 102 mm
Fixing: post top + Ø 48/60 mm bracket, fixed or adjustable with a 15° step / wall-mounted, fixed or adjustable with a 15°
Ø power cable: 10 ÷ 14 mm
Cable gland: PG11

### Flow adjustment

Standard On request

Virtual Midnight Teaching	X
Arrangement for Zhaga connector (Book 18)	X
Adjusting 1-10V	X
DALI control	X
Mains voltage variation	X
Pilot line	X
Power line telemanagement (PLC)	X
Wireless remote management	X
Provision for motion/light sensors	X


### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)
Lenses: PMMA
Seals: extruded anti-age silicone
Screws: stainless steel AISI 304
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors


■ Sablé 100 Noir	Code: <b>06LV3B2098CHM3</b>
------------------	-----------------------------

## Complements




06AK903C0

L3 Joint kit  
single for Ø 60-76 mm poles. Colour:  
Sablé 100 Noir.




06AK904C0

L4 Joint kit  
double for Ø 60-76 mm poles. Colour:  
Sablé 100 Noir.




06AK910C0

L12 Joint for Ø 60-48 mm pole.  
Colour: Sablé 100 Noir.




06AK952C0

L9 Joint LEVANTE SMALL  
for Ø 60 mm pole. Colour: Sablé 100  
Noir.



06AK905C0

B153 Post top joint  
Ø 60 mm (h. 90 mm). Colour: Sablé 100  
Noir.




06AK921C0

B1 Single arm  
Ø 60 mm for poles Ø 60-76 mm. L=550  
mm. Colour: Sablé 100 Noir.




06AK922C0

B2 Double arm  
Ø 60 mm for poles Ø 60-76 mm. L=550  
mm. Colour: Sablé 100 Noir.



06AK951C0

B1-P Wall-mounted arm.  
Colour: Sablé 100 Noir.



06AK906C0

B154 Single arm  
for poles Ø 102 mm. L=245 mm. Colour:  
Sablé 100 Noir.

**Product Sheet**

Rev. 25/03/2022

**Levante Pole Side**


Size: small

Color Temperature: 3000 K

Type of optics: street


**06LV3B2098CHM3**

Colour: Sablé 100 Noir

**06AK908C0**


B156 Double arm

for poles Ø 102 mm. L=245 mm. Colour: Sablé 100 Noir.

**06AK909C0**

B157 Double arm

for poles Ø 102 mm. L=550 mm. Colour: Sablé 100 Noir.

**01AK921C0**

B1 Single tubular arm

Ø 60 mm for poles Ø 60-76 mm. L=550 mm. Colour: Sablé 100 Noir.

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.