





### General Features

|   |
|---|
| Description: modular LED floodlight             |
| Insulation class: class II                      |
| Rated voltage: 220-240 V 50/60 Hz               |
| Protection Grade: IP66                          |
| Impact protection: IK08                         |
| Power Factor: > 0.90                            |
| Ambient temperature Ta: -30°C +50°C             |
| Weight: 26.10 kg                                |
| Max exposed surface: 0,30 m <sup>2</sup>        |
| Lateral exposed surface: 0,08 m <sup>2</sup>    |
| Common mode surge protection: 10 kV             |
| Overvoltage protection differential mode: 10 kV |
| Drivers: included                               |
| Marks and Certifications: ENEC / CE             |



### Performance Data\*

|                       |          |
|-----------------------|----------|
| LED Current:          | 525 mA   |
| Source flow:          | 47655 lm |
| Source power:         | 280 W    |
| Source efficiency:    | 170 lm/W |
| Device flow:          | 40985 lm |
| Device power:         | 311 W    |
| Appliance efficiency: | 132 lm/W |
| Glare Index Category: | D4       |

### Optical System

Source: LED R16

Color Temperature: 3000 K

Color Rendering Index (CRI):  $\geq 70$

Color Consistency (SDCM):  $\leq 4$

Type of optics: asymmetrical LT-05

Optical group life: >160.000h @700mA @Ta25°C TM21  
L80B20 >160.000h @700mA @Ta25°C TM21 L80B10

Photobiological safety class: EXEMPT GROUP

Light intensity category: G\*6

### Normative References

EN60598-1 / EN60598-2-5 / EN62471 / EN61547

### Installation and maintenance

Installation: ceiling / light tower

Fixing: fixed steel bracket AISI 316

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Replaceable wiring plate: removable by unlocking  
fastening clip

Replaceable optical unit: each LED module is replaceable

Power supply compartment: independent from the  
optical group

### Flow adjustment

Standard On request

Virtual Midnight Teaching

X

Constant flow output (CLO)

X

Adjusting 1-10V

X

DALI control

X

Mains voltage variation

X

Pilot line

X

Power line telemanagement (PLC)

X

Wireless remote management

X

Emergency lighting

X

Provision for motion/light sensors

X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper  
content < 1%)

Screen: tempered flat glass

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: self-extinguishable technopolymer V0

Finish: phospho-chromatation treated and polyester  
powder-coated in 16 phases to increase weather resistance

### Colors

■ Grey RAL9006

Code: **06MQ5V25938AHM4**

## Complements



06MQ902XX

Ceiling fixing bracket  
made of AISI 316 stainless steel.



06MQ904XX

Adjustable fixing bracket  
AISI 316 5-10-15°

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of  $\pm 7\%$ .

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.