



### General Features

Description: ceiling-mounted modular LED system

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK08

Power Factor: > 0.90

Ambient temperature Ta: -30°C +50°C

Weight: 14.00 kg

Max exposed surface: 0,16 m<sup>2</sup>

Lateral exposed surface: 0,05 m<sup>2</sup>

Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Drivers: included

Marks and Certifications: ENEC / CE / Resistance to the launch of ball



### Performance Data\*

LED Current:	350 mA
Source flow:	18465 lm
Source power:	92 W
Source efficiency:	201 lm/W
Device flow:	15880 lm
Device power:	102 W
Appliance efficiency:	156 lm/W
Glare Index Category:	D5

### Optical System

Source: LED R8

Color Temperature: 4000 K

Color Rendering Index (CRI):  $\geq 70$

Color Consistency (SDCM):  $\leq 4$

Type of optics: rectangular narrow beam RE-C

Optical group life: >100.000h @700mA @Ta25°C TM21 L80B20

Photobiological safety class: EXEMPT GROUP

Light intensity category: G\*3

### Normative References

EN60598-1 / EN60598-2-1 / EN62471 / EN61547

### Installation and maintenance

Installation: ceiling installation

Fixing: designed for connection systems required by busbar suppliers; steel brackets fastened to ceiling with expansion anchors or chemical bolts; suspension from ceiling with steel cables

Wiring: connecting the system to the power supply line via an external tool-free panel connector means the product does not need to be opened and speeds up installation (in two or three module versions: on request, two separate 230V control gears)

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Power supply compartment: independent from the optical group

### Flow adjustment

Standard On request

Virtual Midnight Teaching

X

Constant flow output (CLO)

X

DALI control

X

Mains voltage variation

X

Pilot line

X

Power line telemanagement (PLC)

X

Wireless remote management

X

Emergency lighting

X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: tempered flat glass

Lenses: high-transparency PMMA

Fixing system: cutted and folded metal sheet bracket

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ White RAL9003

Code: **06MQ1L63087DHM4**

## Complements



06MQ901J

Suspension kit  
ceiling-mounted L=1500 mm.



06MQ900D

Ceiling fixing bracket.  
Colour: white RAL9003.

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.