



**General Features**

- Description: LED fitting for lighting walkways and urban spaces
- Insulation class: class II
- Rated voltage: 220-240 V 50/60 Hz
- Protection Grade: IP66
- Impact protection: IK09
- Surge protection device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM
- Power Factor: > 0.90
- Ambient temperature Ta: -30°C +50°C
- Weight: 4.50 kg
- Max exposed surface: 0,06 m<sup>2</sup>
- Lateral exposed surface: 0,030 m<sup>2</sup>
- Common mode surge protection: 10 kV
- Overvoltage protection differential mode: 10 kV
- Driver: included
- Driver lifetime: >100.000 h @ Ta 25°C (0,2% / 1000h)
- Marks and Certifications: CE



**Performance Data\***

|                       |          |
|-----------------------|----------|
| Source flow:          | 2495 lm  |
| Source power:         | 13 W     |
| Source efficiency:    | 192 lm/W |
| Device flow:          | 2135 lm  |
| Device power:         | 16 W     |
| Appliance efficiency: | 133 lm/W |
| Glare Index Category: | D6       |

**Optical System**

|  |
|--|
| Source: LED R1                                       |
| Color Temperature: 2700 K                            |
| Color Rendering Index (CRI): $\geq 70$               |
| Chromatic consistency (SDCM): $\leq 3$               |
| Type of optics: LT-64 Asymmetric beam with backlight |
| Optical group life: >100.000 h @ Ta 25°C L90B10      |
| Photobiological safety class: EXEMPT GROUP           |
| ULOR: 0%   |
| DLOR: 100%   |
| Light intensity category: G*3                        |
| BUG rating: B1-U0-G1                                 |

**Normative References**

|   |
|---|
| EN60598-1 / EN60598-2-3 / EN62471 / EN61547 |
|---|

**Installation and maintenance**

|   |
|---|
| Installation: pole side                                       |
| Tilt: continuous adjustment                                   |
| Fixing: arm $\varnothing$ 48 mm                               |
| Wiring: pre-wired product                                     |
| $\varnothing$ power cable: 10 ÷ 14 mm                         |
| Cable Gland: PG16   |
| Replaceable wiring plate: removable plate                     |
| Replaceable optical unit: LED disc replacement                |
| Power supply compartment: independent from the optical system |

**Flow adjustment**

On request

|                           |   |
|---------------------------|---|
| Virtual Midnight Teaching | X |
| DALI control              | X |

**Materials**

|  |
|--|
| Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)   |
| Screen: tempered flat glass  |
| Lenses: high-transparency PMMA   |
| Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)                                |
| Seals: expanded anti-age silicone foam   |
| Screws: stainless steel AISI 304   |
| Wiring plate: zinc-plated steel  |
| Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance |

**Colors**

|   |                               |
|---|-------------------------------|
|  Sablé 100 Noir | Code: <b>06ND1B230825CHM4</b> |
|---|-------------------------------|

## Complements



06ND901Y0

Diffuser  
made of transparent polycarbonate

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.