



**General Features**

Description:	LED floodlight
Insulation class:	class II
Rated voltage:	220-240 V 50/60 Hz
Protection Grade:	IP66
Impact protection:	IK07
Power Factor:	> 0.9
Ambient temperature Ta:	-30°C +50°C
Weight:	1.5 kg
Max exposed surface:	0,011 m <sup>2</sup>
Lateral exposed surface:	0,006 m <sup>2</sup>
Driver:	included
Marks and Certifications:	CE



**Performance Data\***

Source flow:	600 lm
Source power:	6.2 W
Source efficiency:	97 lm/W
Device flow:	215 lm
Device power:	7.8 W
Appliance efficiency:	28 lm/W
Glare Index Category:	D6

**Product Sheet**

Rev. 17/01/2023

**Omikron mini Bollard**

Options: ON-OFF

Color Temperature: 3000 K

Type of optics: U-D 90° Diffused beam

**06OM5A139C4A**

Colour: Grey RAL9006

**Optical System**

Source: LED

Color Temperature: 3000 K

Color Rendering Index (CRI):  $\geq 80$ Chromatic consistency (SDCM):  $\leq 3$ 

Type of optics: U-D 90° Diffused beam

Optical group life: &gt;100.000h @Ta25°C L80B10

Photobiological safety class: EXEMPT GROUP

**Normative References**

EN60598-1 / EN60598-2-5 / EN62471 / EN61547

**Installation and maintenance**

Installation: ground

Pole diameter:  $\varnothing$  30mm

Tilt: -90° +45°, continously-adjustable pointing and locking system

Fixing: base plate made of sheet steel for fixing with screw anchors or anchoring bolts (to be ordered separately).

Bollard made of aluminium alloy EN AW 6026.

Wiring: pre-wired product, cable L=1,5m

Cable Gland: M12x1,5

**Materials**

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content &lt; 1%)

Screen: acid-etched glass

Lenses: high-transparency PMMA

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

**Colors** Grey RAL9006Code: **06OM5A139C4A**

---

**Product Sheet**

Rev. 17/01/2023

**Omikron mini Bollard**

Options: ON-OFF

Color Temperature: 3000 K

Type of optics: U-D 90° Diffused beam

**06OM5A139C4A**Colour: Grey RAL9006

---

**Complements**

---



06GC902X0

B165 2-pole connector IP68

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.