




General Features

Description:	Wall-mounted mono and bi-emission product
Insulation class:	class I
Rated voltage:	230 V 50 Hz
Protection Grade:	IP65
Impact protection:	IK05
Power Factor:	> 0.90
Ambient temperature Ta:	-30°C +50°C
Weight:	2.00 kg
Max exposed surface:	0,058 m²
Lateral exposed surface:	0,035 m²
Driver:	included
Marks and Certifications:	CE



H (m)	Ø (m)	Em(lux)
1	0,19	5448
2	0,37	1362
3	0,56	605
4	0,74	340
5	0,93	218

Performance Data\*

LED Current:	500 mA
Source flow:	695 lm
Source power:	6 W
Source efficiency:	116 lm/W
Device flow:	500 lm
Device power:	7 W
Appliance efficiency:	71 lm/W

## Product Sheet

Rev. 16/07/2024

## One4two Wall-Mounted

Size: small

Color Temperature: 4000 K

Type of optics: C 8° Narrow beam

## 06OT2A4404C

Colour: Sablé 100 Noir

### Optical System

Source: 4 LEDs

Color Temperature: 4000 K

Color Rendering Index (CRI):  $\geq 80$

Chromatic consistency (SDCM):  $\leq 3$

Type of optics: C 8° Narrow beam

Optical group life: >60.000h @Ta25°C L80B10

### Normative References

EN60598-1 / EN60598-2-1 / EN62471

### Installation and maintenance

Installation: wall-mounted

Fixing: With a die-cast aluminium shelf

Ø power cable: 7 ÷ 11 mm

Cable gland: PG11

### Materials

Body: extruded aluminium alloy UNI 9006/T6

Screen: tempered flat glass

Lenses: high-transparency PMMA

Seals: extruded anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ Sablé 100 Noir

Code: **06OT2A4404C**

---

**Product Sheet**

Rev. 16/07/2024

**One4two Wall-Mounted**

Size: small

Color Temperature: 4000 K

Type of optics: C 8° Narrow beam

**06OT2A4404C**Colour: Sablé 100 Noir

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.