



General Features

Description: LED fitting for lighting façades, paths and urban spaces

Insulation class: class III

Rated voltage: 24Vdc

Protection Grade: IP66

Impact protection: IK09

Power Factor: > 0.9

Ambient temperature Ta: -20°C +50°C



Weight: 2.4 kg

Max exposed surface: 0.019 m²

Lateral exposed surface: 0.036 m²

Drivers: remote (to be ordered separately)

Marks and Certifications: CE / ENEC pending



Performance Data*

LED Current:	350 mA
Source flow:	1630 lm
Source power:	13 W
Source efficiency:	125 lm/W
Device flow:	980 lm
Device power:	15 W
Appliance efficiency:	65 lm/W
Glare Index Category:	D6

Product Sheet

06/06/2024

Spoon Applique

Size: small

Options: DALI

Color Temperature: 3000 K

Type of optics: U-D 90° Diffused beam

06SN3A1359B2G6V

Colour: Champagne

Optical System

Source: CoB LED

Color Temperature: 3000 K

Color Rendering Index (CRI): ≥ 90 Color Consistency (SDCM): ≤ 3

Type of optics: U-D 90° Diffused beam

Optical group life: $> 100.000 \text{ h @ } 350\text{mA @ Ta } 25^\circ \text{ C TM21 L80B10}$

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G*6

BUG rating: B1-U0-G0

Normative References

EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547

Installation and maintenance

Installation: wall

Tilt: $-120^\circ \div 30^\circ$ \varnothing power cable: $3,5 \div 7 \text{ mm}$

Cable Gland: M12x1,5

Power supply compartment: independent from the optical group

Flow adjustment

Standard

DALI control

X

MaterialsBody: die-cast aluminium alloy UNI EN AB 47100 (copper content $< 1\%$)

Screen: acid-etched glass

Lenses: highly transparent technopolymer lenses

Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content $< 1\%$)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: zinc-plated steel

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

Colors ChampagneCode: **06SN3A1359B2G6V**

Product Sheet

06/06/2024

Spoon Applique

Size: small

Options: DALI


Color Temperature: 3000 K

Type of optics: U-D 90° Diffused beam

06SN3A1359B2G6V

Colour: Champagne

Complements



06SN901X0

D18 Kit DALI driver

30W 350mA IP67 (N. 1 Spoon Small)

NOTES

*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.