




General Features

Description: LED fitting for lighting façades, paths and urban spaces

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK09

Power Factor: > 0.9

Ambient temperature Ta: -25° C + 50°C

Weight: 8 kg

Max exposed surface: 0.147 m²

Lateral exposed surface: 0.067 m²

Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Driver: included

Driver lifetime: > 100.000 h @Ta 25° C

Marks and Certifications: CE / ENEC

Performance Data*	LA-03_1800K	LA-03_2200K	LA-03_2700K	LA-03_3000K	LA-03_4000K
LED Current:	400 mA	400 mA	400 mA	400 mA	400 mA
Source flux:	2590 lm	3050 lm	3295 lm	3355 lm	3570 lm
Source power:	19 W	19 W	19 W	19 W	19 W
Source efficiency:	136 lm/W	161 lm/W	173 lm/W	177 lm/W	188 lm/W
Device flux:	2175 lm	2560 lm	2765 lm	2815 lm	2995 lm
Device power:	24 W	24 W	24 W	24 W	24 W
Appliance efficiency:	91 lm/W	107 lm/W	115 lm/W	117 lm/W	125 lm/W
Glare Index Category:	D6	D5	D5	D5	D5

Optical System	Flow adjustment	Standard
Source: LED R1	DALI control	X
Color Temperature: ECL 1800K - 4000 K		
Color Rendering Index (CRI): ≥ 80		
Chromatic consistency (SDCM): ≤ 3	Materials	
Type of optics: LA-03 Wide street ECL	Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)	
Optical group life: > 100.000 h @ 720mA @Ta 25° C TM21 L90B10	Screen: tempered flat glass	
Photobiological safety class: EXEMPT GROUP	Lenses: high-transparency PMMA	
ULOR: 0%	Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)	
DLOR: 100%	Seals: anti-age silicone foam	
Light intensity category: G*6	Screws: stainless steel AISI 304	
Normative References	Wiring plate: zinc-plated steel	
EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547	Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance	
Installation and maintenance	Colors	
Installation: wall	■ Champagne	Code: 06SP1BB240417G6DYN
Tilt: 0° ÷ -90°		
Ø power cable: 6 ÷ 11 mm		
Cable Gland: PG13,5		
Power supply compartment: independent from the optical group		

Product Sheet

Rev 16/07/2024

Spoon Applique

Size: large

Color Temperature: ECL 1800K - 4000 K

Type of optics: LA-03 Wide street ECL

06SP1BB240417G6DYNColour: Champagne

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.