

Spoon Applique

Size: large
Color Temperature: 3000 K
Type of optics: ST-02 Narrow street

06SP1BC454914G6HL
Colour: Champagne



General Features

Description: LED fitting for lighting façades, paths and urban spaces

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK09

Power Factor: > 0.9

Ambient temperature Ta: -25° C + 50°C

Weight: 8 kg

Max exposed surface: 0.147 m²

Lateral exposed surface: 0.067 m²



Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Drivers: included

Lifetime driver: > 100.000 h @Ta 25° C

Marks and Certifications: CE / ENEC pending



Performance Data*

Source flow:	8700 lm
Source power:	49 W
Source efficiency:	178 lm/W
Device flow:	7300 lm
Device power:	53 W
Appliance efficiency:	138 lm/W
Glare Index Category:	D4

Optical System
Source: LED R2
Color Temperature: 3000 K
Color Rendering Index (CRI): ≥ 80
Color Consistency (SDCM): ≤ 3
Type of optics: ST-02 Narrow street
Optical group life: > 100.000 h @ 720mA @Ta 25° C TM21 L90B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Light intensity category: G*3
BUG rating: B2-U0-G1
Normative References
EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547
Installation and maintenance
Installation: wall
Tilt: 0° ÷ -90°
Ø power cable: 6 ÷ 11 mm
Cable Gland: PG13,5
Power supply compartment: independent from the optical group

Flow adjustment	Standard	On request
Virtual Midnight Teaching		X
Arrangement for Zhaga connector (Book 18)		X
DALI control	X	
Materials		
Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)		
Screen: tempered flat glass		
Lenses: high-transparency PMMA		
Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)		
Seals: anti-age silicone foam		
Screws: stainless steel AISI 304		
Wiring plate: zinc-plated steel		
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance		
Colors		
<div>■ Champagne</div>	Code:	06SP1BC454914G6HL

Product Sheet

06/06/2024

Spoon Applique

Size: large

Color Temperature: 3000 K

Type of optics: ST-02 Narrow street

06SP1BC454914G6HLColour: Champagne

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.