



General Features

Description: LED fitting for lighting façades, paths and urban spaces

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK09

Power Factor: > 0.9

Ambient temperature Ta: -25° C + 50° C

Weight: 11 kg

Max exposed surface: 0.212 m<sup>2</sup>

Lateral exposed surface: 0.086 m<sup>2</sup>

Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Drivers: included

Lifetime driver: > 100.000 h @Ta 25° C

Marks and Certifications: CE / ENEC pending



Performance Data\*

Source flow:	11740 lm
Source power:	75 W
Source efficiency:	157 lm/W
Device flow:	9890 lm
Device power:	70 W
Appliance efficiency:	141 lm/W
Glare Index Category:	D4

<b>Optical System</b>
Source: LED R4
Color Temperature: 3000 K
Color Rendering Index (CRI): ≥ 80
Color Consistency (SDCM): ≤ 3
Type of optics: ST-02 Narrow street
Optical group life: > 100.000 h @ 720mA @Ta 25° C TM21 L90B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Light intensity category: G*3
BUG rating: B2-U0-G2
<b>Normative References</b>
EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547
<b>Installation and maintenance</b>
Installation: wall
Tilt: 0° ÷ -90°
Ø power cable: 6 ÷ 11 mm
Cable Gland: PG13,5
Power supply compartment: independent from the optical group

<b>Flow adjustment</b>	Standard	On request
Virtual Midnight Teaching		X
Arrangement for Zhaga connector (Book 18)		X
DALI control	X	
<b>Materials</b>		
Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)		
Screen: tempered flat glass		
Lenses: high-transparency PMMA		
Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)		
Seals: anti-age silicone foam		
Screws: stainless steel AISI 304		
Wiring plate: zinc-plated steel		
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance		
<b>Colors</b>		
<div><div></div> Champagne</div>	Code:	06SP1CE836914G6HL

---

**Product Sheet**

06/06/2024

**Spoon Applique**

Size: x-large

Color Temperature: 3000 K

Type of optics: ST-02 Narrow street

**06SP1CE836914G6HL**Colour: Champagne

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.