



General Features

| |
|---|
| Description: LED fitting for lighting façades, paths and urban spaces |
| Insulation class: class II |
| Rated voltage: 220-240 V 50/60 Hz |
| Protection Grade: IP66 |
| Impact protection: IK09 |
| Power Factor: > 0.9 |
| Ambient temperature Ta: -25° C + 50°C |
| Weight: 11 kg |
| Max exposed surface: 0.212 m² |
| Lateral exposed surface: 0.086 m² |
| Common mode surge protection: 10 kV |
| Overvoltage protection differential mode: 10 kV |
| Drivers: included |
| Lifetime driver: > 100.000 h @Ta 25° C |
| Marks and Certifications: CE / ENEC pending |



Performance Data*

| | |
|-----------------------|----------|
| Source flow: | 15310 lm |
| Source power: | 98 W |
| Source efficiency: | 156 lm/W |
| Device flow: | 12870 lm |
| Device power: | 93 W |
| Appliance efficiency: | 138 lm/W |
| Glare Index Category: | D5 |

Product Sheet

06/06/2024

Spoon Applique

Size: x-large

Color Temperature: 3000 K

Type of optics: LT-63 Asymmetric beam

06SP1CE848915G6HL

Colour: Champagne

Optical System

Source: LED R4

Color Temperature: 3000 K

Color Rendering Index (CRI): ≥ 80 Color Consistency (SDCM): ≤ 3

Type of optics: LT-63 Asymmetric beam

Optical group life: > 100.000 h @ 720mA @Ta 25° C TM21 L90B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G*6

BUG rating: B2-U0-G2

Normative References

EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547

Installation and maintenance

Installation: wall

Tilt: 0° ÷ -90°

Ø power cable: 6 ÷ 11 mm

Cable Gland: PG13,5

Power supply compartment: independent from the optical group

Flow adjustment

Standard On request

Virtual Midnight Teaching

X

Arrangement for Zhaga connector (Book 18)

X

DALI control

X

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: tempered flat glass

Lenses: high-transparency PMMA

Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Seals: anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: zinc-plated steel

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

Colors ChampagneCode: **06SP1CE848915G6HL**

Product Sheet

06/06/2024

Spoon Applique

Size: x-large

Color Temperature: 3000 K

Type of optics: LT-63 Asymmetric beam

06SP1CE848915G6HLColour: Champagne

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of $\pm 7\%$.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.