



General Features

Description: LED fitting for lighting paths and urban spaces

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66


Impact protection: IK09

Power Factor: > 0.9

Ambient temperature Ta: -20°C +50°C

Driver: included

Marks and Certifications: CE / ENEC



Performance Data*

Product Sheet

Rev 16/07/2024

Spoon System

Size: 3 Spoon Small
Options: System 1 ON-OFF
Color Temperature: 3000 K
Type of optics: Projection optics

06SP0A90001C10G6

Colour: Champagne

Optical System

Source: CoB LED

Color Temperature: 3000 K

Color Rendering Index (CRI): ≥ 90 Chromatic consistency (SDCM): ≤ 3

Type of optics: Projection optics

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Normative References

EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 /
EN61547

Installation and maintenance

Installation: pole

Tilt: +120° -60°

Ø power cable: 3,5 ÷ 7 mm

Cable Gland: M12x1,5

Power supply compartment: independent from the
optical group

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper
content < 1%)

Screen: tempered flat glass

Lenses: highly transparent technopolymer lenses


Fixing system: die-cast aluminium alloy UNI EN AB 47100
(copper content < 1%)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: zinc-plated steel

Finish: phospho-chromatation treated and polyester
powder-coated in 16 phases to increase weather resistance

Colors ChampagneCode: **06SP0A90001C10G6**

Product Sheet

Rev 16/07/2024

Spoon System

Size: 3 Spoon Small

Options: System 1 ON-OFF

Color Temperature: 3000 K

Type of optics: Projection optics

06SP0A90001C10G6Colour: Champagne

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.