




General Features

Description: LED fitting for lighting paths and urban spaces
Insulation class: class II
Rated voltage: 220-240 V 50/60 Hz
Protection Grade: IP66
Impact protection: IK09
Power Factor: > 0.9
Ambient temperature Ta: -25°C +50°C
Driver: included
Marks and Certifications: CE / ENEC



Performance Data*

Optical System	Flow adjustment	Standard
Source: LED	DALI control	X
Color Temperature: 3000 K		
Color Rendering Index (CRI): ≥ 80		
Chromatic consistency (SDCM): ≤ 3	Materials	
Type of optics: Projection optics	Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)	
Photobiological safety class: EXEMPT GROUP	Screen: tempered flat glass	
ULOR: 0%	Lenses: high-transparency PMMA	
DLOR: 100%	Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)	
Normative References	Seals: anti-age silicone foam	
EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547	Screws: stainless steel AISI 304	
	Wiring plate: zinc-plated steel	
	Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance	
Installation and maintenance	Colors	
Installation: pole	<div>Champagne</div>	Code:
Tilt: 0° +90°		06SP0C90001C10G6HL
Ø power cable: 6 ÷ 11 mm		
Cable Gland: PG13,5		
Power supply compartment: independent from the optical group		

Product Sheet

Rev 16/07/2024

Spoon System

Size: 3 Spoon Medium

Options: System 3 PROJECTION OPTICS

Color Temperature: 3000 K

Type of optics: Projection optics

06SP0C90001C10G6HL

Colour: Champagne

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.