




General Features

| | |
|---------------------------|---|
| Description: | ceiling / wall / ground-mounted LED product |
| Insulation class: | class III |
| Rated voltage: | 24Vdc |
| Protection Grade: | IP67 |
| Impact protection: | IK08 |
| Power Factor: | > 0.90 |
| Ambient temperature Ta: | -10°C +45°C |
| Weight: | 6.00 kg |
| Driver: | remote (to be ordered separately) |
| Marks and Certifications: | ENEC / CE |



Performance Data*

| | |
|-----------------------|---------|
| Source flow: | 1800 lm |
| Source power: | 19 W |
| Source efficiency: | 95 lm/W |
| Device flow: | 1480 lm |
| Device power: | 19 W |
| Appliance efficiency: | 78 lm/W |
| Glare Index Category: | D6 |

Product Sheet

Rev. 17/01/2023

Trail Walk Over Recessed

Size: L. 1250mm

Color Temperature: 4000 K

Type of optics: asymmetrical $\alpha=13^\circ 30'/75^\circ$ **06TR3H2307J**Colour: natural anodized
aluminium**Optical System**

Source: LED

Color Temperature: 4000 K

Color Rendering Index (CRI): ≥ 80 Color Consistency (SDCM): ≤ 3 Type of optics: asymmetrical $\alpha=13^\circ 30'/75^\circ$

Optical group life: >60.000h @Ta25°C L80B10

Light intensity category: G*6

Normative References

EN60598-1 / EN60598-2-1 / EN60598-2-2 / EN62471

Installation and maintenance

Installation: ceiling / wall / ground (outside or recessed)

Fixing: recessed housing (wall / ground recessed);
adjustable brackets / junction box / junction box with
adjustable brackets / ceiling-mounted bracket /
suspension kit (for outdoor installation)

Wiring: pre-wiring with cable L=1500 mm

Ø power cable: bipolar cable 2x0.5 mm² and related
connector (included)**Flow adjustment**

On request

Adjusting 1-10V

X

DALI control

X

Materials

Body: extrusion and further anodization

Diffuser: transparent flat glass (walkable version up to 1000
kg)

Lenses: highly transparent technopolymer lenses

Fixing system: closing heads and fastening accessories
made of die-cast aluminium alloy UNI EN AB 47100
(copper content < 1%)

Seals: extruded anti-age silicone

Screws: stainless steel AISI 304

Colors natural anodized
aluminiumCode: **06TR3H2307J**

Product Sheet

Rev. 17/01/2023

Trail Walk Over Recessed

Size: L. 1250mm


Color Temperature: 4000 K

Type of optics: asymmetrical $\alpha=13^\circ 30'/75^\circ$ **06TR3H2307J**Colour: natural anodized
aluminium**Complements**

06TA902X0

Driver
60W-24V IP66

06LL915AB0

Driver
240W-24V IP67

06TR999J0

Recessed housing
for ground recessed and wall
installation, with IP68 connector

06AK958X0

M3 Kit in/out
cable 2x0,75 L=1000 mm with junction
box

06LL914AB0

DALI driver
150W-24V IP67**NOTES*****Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.